



EAGLE TX/SM SC

Industrial Networking:Industrial Ethernet:EAGLE System:EAGLE Firewall with VPN

Product description	
Description	Industrial Firewall/VPN System
Modi	Router, Single Client Transparent (SCT) and Multi Client Transparent(MCT), PPPoE, PPTP
Port type and quantity	Trusted Port: 1 x 10/100BASE-TX, TP-cable, RJ45-socket, autocrossing, autonegotiation, autopolarity Untrusted Port: 1 x 100BASE-FX, SM-cable, SC-socket
Type	EAGLE TX/SM SC
Order No.	943 011-303
More Interfaces	
Power supply/signaling contact	1 plug-in terminal block, 6-pin
V.24 interface	1 x RJ11 socket
Network size - length of cable	
Twisted pair (TP)	0 - 100 m
Single mode fiber (SM)9/125 µm	0 - 32.5 km, 16 dB link budget at 1300 nm, A = 0.4 dB/km, 3 dB reserve, D = 3.5 ps/(nm x km)
Security	
Stateful inspection firewall	firewallrules (incoming/outgoing, modem access, management), IP masquerading, 1-to-1 NAT, ARP limiter, MAC filter
Multipoint VPN	IPSec, L2TP, DES, 3DES, AES (-128, -192, -256), Pre-Shared Key, X.509v3 certificate, MD5, SHA-1, NAT-T, firewall rules for every VPN connection
Antivirus protection	Kaspersky anti virus engine (HTTP, FTP, POP3, SMTP)
Power requirements	
Operating voltage	24 V DC (-25% to +30%)
Current consumption at 24 V DC	max. 350 mA
Service	
Diagnostics	LEDs (power, link status, data, error, ACA) signaling contact (24 V DC / 1 A), logfile
Configuration	Command Line Interface (CLI), web interface, auto configuration adapter (ACA11), HiDiscovery, SolSoft policy server (ISCM)
Other services	DHCP server/client, DHCP Relay/Option 82, DynDNS, firewall access via V.24 (PPP), NTP, VLAN support (IEEE 802.3pQ), port forwarding serial, HTTPS, SSH,SNMP V1/V2/V3, LLDP (HiVision/ Industrial HiVision)
Redundancy	
Redundancy functions	use in redundant net-/ringcoupling, dual homing, firewall redundancy (VRRP), redundant 24 V power supply
Ambient conditions	
Operating temperature	0 °C to +55 °C
Storage/transport temperature	-40 °C to +80 °C
Relative humidity (non-condensing)	10% to 95%
MTBF	25.18 years; MIL-HDBK 217F: Gb 25 °C
Mechanical construction	
Dimensions (W x H x D)	47 mm x 131 mm x 111 mm
Mounting	DIN Rail 35 mm
Weight	340 g

Protection class	IP 20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13,2 Hz, 90 min.; 0,7g, 13,2 Hz - 100 Hz, 90 min.; 3,5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 2000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (linie/earth), 1 kV (linie/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508 in preparation
Hazardous locations	cUL 1604 Class1 Div 2 in preparation
Germanischer Lloyd	Germanischer Lloyd
Scope of delivery and accessories	
Scope of delivery	device, terminal block, operating instructions, CD-manual
Accessories to order separately	rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, terminal cable, modem cable, HiVision network management, auto-configuration adapter (ACA 11), 19" installation frame