



MS4128-L3E

Industrial Networking:Industrial Ethernet:MICE:Switches

Product description	
Description	Power MICE, modular, managed Industrial ETHERNET Switch, Layer 3 Switch with Software Enhanced. ETHERNET (10 Mbit/s) and Fast-ETHERNET (100 Mbit/s) and Gigabit-ETHERNET (1000 Mbit/s)
Port type and quantity	up to 28 ports above media modules practicable, 4 X 1000 BASE-SX with SFP modules or 4 x 10/100/1000 BASE-TX and 24 Fast-ETHERNET (100 Mbit/s) ports (with MB-2T)
Type	MS4128-L3E
Order No.	943 009-201
More Interfaces	
Power supply/signaling contact	2 plug-in terminal blocks, 4-pin
V.24 interface	1 x RJ11 socket
USB interface	1 USB interface to connect auto-configuration adapter (ACA21-USB)
Network size - cascading	
Line - / star topology	any
Ring structure (HIPER-Ring)	50 switches (reconfiguration time < 50 ms typ. at LWL)
Power requirements	
Operating voltage	24 V DC (-25% to +30%)
Current consumption at 24 V DC	630 mA (without media modules)
Power consumption	15 W (without media modules)
Service	
	serial interface, web interface, SNMP V1/V2/V3, HiVision, file transfer SW HTTP/TFTP
Diagnostics	LEDs, signal contact (24V DC / 1 A), syslog, logfile, RMON, port mirroring, Topology Discovery IEEE 802.1AB (LLDP)
Configuration	command line interface (CLI), TELNET, BootP, DHCP, DHCP Option 82, HiDiscovery, auto-configuration adapter (ACA21-USB)
Security	authentication 802.1x, port-security IP and MAC, SNMP V3, ACL (L2/L3/L4 packet filtering) 20 / port
Other services	QoS 8 classes, port prioritisation IEEE 802.1D/p, VLAN IEEE 802.1Q, Multicast (IGMP Snooping/Querier), GMRP, Broadcast- UC-, MC-Limiter, Fast Aging, Flow Control IEEE 802.3x, PTP client (Precision Time Protocol, IEEE 1588), SNTP (Simple Network Time Protocol), Traffic Shaping, protocol based VLANs static routing, dynamic routing (RIP V1/2), VRRP,
Redundancy	
Redundancy functions	HIPER-Ring (ring structure), RSTP IEEE 802.1w (rapid spanning tree protocol), redundant network/ring coupling (master/receiver functionality), dual homing (master/receiver functionality), redundant 24 V power supply
Ambient conditions	
Operating temperature	0 °C to +60 °C
Storage/transport temperature	-25 °C to +70 °C
Relative humidity (non-condensing)	10% to 95%
MTBF	24.2 years; MIL-HDBK 217F: Gb 25 °C
Mechanical construction	
Dimensions (W x H x D)	315 mm x 134 mm x 140 mm
Mounting	DIN Rail
Weight	2,2 kg
Protection class	IP 20
Mechanical stability	

IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7 g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	cUL 1604 Class 1 Div 2
Germanischer Lloyd	Germanischer Lloyd
Railway norm	EN50121-4
Scope of delivery and accessories	
Scope of delivery	device, 2 terminal block, operating manual
Accessories to order separately	rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, terminal cable, HiVision network management, auto-configuration adapter (ACA21-USB), 19" installation frame, labels ML-MS2/MM, additional backplane MB-2T