



## OZD 485 G12 BAS

Industrial Networking:FiberINTERFACES:Field Bus:RS 485 Repeaters

### Product description

Description	interface converter electrical/optical for RS 485 field bus networks; repeater function; for quartz glass FO; electrical semi-duplex mode
Port type and quantity	2 x optical: BFOC 2.5 (STR) socket 1 x electrical: 6-pin terminal block
Type	OZD 485 G12 BAS
Order No.	943 893-321

### Electrical interface

Signal type	RS 485
Input resistance	10 kOhm
Input voltage range	-7 V ... +12 V
Jitter	typ. 10 nspp
Distortion of bit duration	typ. 1 nspp
Bit rate	0 to 1.5 Mbit/s NRZ

### Optical interface

Wavelength	860 nm
Optical input power	-30 dBm

### More Interfaces

Power supply	5-pin terminal block
Signaling contact	-
Voltage output	-

### Network size - length of cable

Single mode fiber (SM) 9/125 µm	-
Multimode fiber (MM) 50/125 µm	2300 m 10 dB link budget at 860 nm; A = 3 dB/km, 3 dB reserve
Multimode fiber (MM) 62.5/125 µm	3100 m 14 dB link budget at 860 nm; A = 3.5 dB/km, 3 dB reserve

System delay time	<1,56 us
-------------------	----------

### Power requirements

Operating voltage	18 ... 32 VDC (typ. 24 VDC)
Current consumption	80 mA at 24 VDC, 65 mA at 32 VDC
Power consumption	<2,1 W

### Redundancy

Redundancy functions	-
----------------------	---

### Ambient conditions

Operating temperature	0 °C to +60 °C
Storage/transport temperature	-25 °C to +80 °C
Relative humidity	<95% (non-condensing)

### Mechanical construction

Dimensions (W x H x D)	35 x 156 x 119
Mounting	DIN rail
Weight	180 g
Protection class	IP 20
Housing material	plastics

### Approvals

Issued or requested approvals	C-Tick
-------------------------------	--------

### Scope of delivery and accessories

Scope of delivery

device, start-up instructions

Accessories to order separately

manual, order no. 039 516-001