



OZD Profi 12M P11 PRO

Industrial Networking:FiberINTERFACES:Field Bus:Profibus Rail Repeaters

Product description

Description	interface converter electrical/optical for PROFIBUS-field bus networks; repeater function; for plastic FO; short-haul version;
Port type and quantity	1 x optical: 2 sockets BFOC 2.5 (ST®) 1 x electrical: Sub-D 9-pin, female, pin assignment according to EN 50170 part 1
Type	OZD Profi 12M P11 PRO
Order No.	943 904-221

Electrical interface

Signal type	PROFIBUS (DP-V0, DP-V1, DP-V2 und FMS)
Bit rate	9.6; 19.2; 45.45; 93.75; 187.5; 500 kbit/s; 1.5; 3; 6; 12 Mbit/s (automatic setting)
Signal delay time (optional input/output)	<= 6.5 bit times
Input/output signal	RS 485 level
Input voltage range	-7 V ... +12 V
Galvanic isolation	no

Optical interface

Wavelength	660 nm
Cascadability	not limited

More Interfaces

Power supply	5-pin terminal block, screw mounting
Signaling contact	5-pin terminal block, screw mounting
Measuring outputs "Optical input power"	3-pin terminal block, screw mounting

Network size - length of cable

Single mode fiber (SM) 9/125 µm	-
Multimode fiber (MM) 50/125 µm	-
Multimode fiber (MM) 62.5/125 µm	-
Multimode fiber HCS (MM) 200/230 µm	400 m 8 dB link budget at 660 nm and transmitting power default A = 8 dB/km, 2 dB reserve
Multimode fiber POF (MM) 980/1000 µm	50 m 15 dB link budget at 660 nm and transmitting power reduced 80 m 20 dB link budget at 660 nm and transmitting power default A = 0.2 dB/m, 2 dB reserve

Power requirements

Operating voltage	18 ... 32 VDC, typ. 24 VDC
Galvanic isolation	yes
Current consumption	max. 200 mA
Power consumption	4.8 W
Output voltage/output current (pin6)	5 VDC +5%, -10%, short circuit-proof/90 mA

Redundancy

Redundancy functions	redundant 24 V infeed
----------------------	-----------------------

Ambient conditions

Operating temperature	0 °C to +60 °C
Storage/transport temperature	-40 °C to +70 °C
Relative humidity	<95% (non-condensing)

Mechanical construction

Dimensions (W x H x D)	35 x 156 x 119 mm
------------------------	-------------------

Mounting	DIN rail
Weight	200 g
Protection class	IP 20
Housing material	plastics

Approvals

Issued or requested approvals	cUL508, cUL1604 Class1, Div. 2, Groups A,B,C and D; according to directive 94/9/EG (ATEX 95): Ex II 3 G (Zone 2); C-Tick
-------------------------------	--

Scope of delivery and accessories

Scope of delivery	device, 2 optical BFOC ST plugs, start-up instructions
Accessories to order separately	manual, order no. 039 690-001