



## RPS 120 EEC

Industrial Networking:Industrial Ethernet:System Accessories:Power supply

Product description	
Description	24 V DC DIN rail power supply unit
Type	RPS 120 EEC
Order No.	943 662-120
More Interfaces	
Voltage input	1 Bi-stable, quick-connect spring clamp terminals, 3-pin
Voltage output	1 Bi-stable, quick-connect spring clamp terminals, 6-pin
Power requirements	
Operating voltage	230 V
Input data	
230 V	100-240 V AC (-15/+10%); 50-60Hz or 110 to 300 V DC (+/-20%)
Current consumption	
230 V	max. 1,4-0,65 A at 100-240 V AC max. 1,2 - 0,45 A bei 120 - 300 V DC < 15 A at 100 and 230 V AC
Activation current	< 15 A at 100 and 230 V AC
Output data	
Output voltage	24-28 V DC (typ. 24,1 V); externally adjustable
Output current	
230 V	min. 5 - 4,5 A continuous 7,5 - 6,7 A for typ. 4 sec
Service	
Diagnostics	LED (DC OK, Overload)
Redundancy	
Redundancy functions	Power supply units can be connected in parallel
Ambient conditions	
Operating temperature	-25 °C to +70 °C (ab 60 °C Derating)
Storage/transport temperature	-40 °C to +85 °C
Relative humidity (non-condensing)	5 to 95 %
MTBF	-
Mechanical construction	
Dimensions (W x H x D)	40 mm x 124 mm x 117 mm
Mounting	DIN Rail 35 mm
Weight	620 g
Protection class	IP 20
EMC interference immunity	
EN 50082-1	EN 61000-6-1
EN 50082-2	EN 61000-6-2 (includes EN 55024)
EMC emitted immunity	
EN 50081-1	EN 61000-3-2, 61000-3-3, 61000-6-3, 61000-6-4
EN 50081-2	-
Approvals	
Safety of industrial control equipment	cUL 508 (E 198865)
Safety of information technology equipment	cUL 60950 (E 137006)
Hazardous locations	UL 1604 Class 1 Div. 2 (E246877)
Scope of delivery and accessories	

Scope of delivery

Rail power supply,  
Description and operating manual