



## RS20-2500MMM2SDAUHH

Industrial Networking:Industrial Ethernet:OpenRail System:Compact:Unmanaged Switches

<b>Product description</b>	
Description	Fast ETHERNET-switch according to IEEE 802.3 compact, unmanaged, Industrial switch for DIN rail store-and-forward-switching, fanless design, ports: 25 x FE
Port type and quantity	25 ports in total; 1. Uplink Port: 2 x 100BASE-FX, MM-SC; 2. Uplink Port: 100BASE-FX, MM-SC, 22 x standard 10/100 BASE TX, RJ45
Type	RS20-2500MMM2SDAUHH
Order No.	RS20-2500MMM2SDAUHH
<b>More Interfaces</b>	
Power supply/signaling contact	1 x plug-in terminal block, 6-pin
<b>Network size - length of cable</b>	
Multimode fiber (MM) 50/125 µm	0 - 5000 m, 8 dB link budget at 1300 nm, A = 1 d/km, 3 dB reserve, B = 800 MHz x km
Multimode fiber (MM) 62.5/125 µm	0 - 4000 m, 11 dB link budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 500 MHz x km
<b>Network size - cascading</b>	
Line - / star topology	any
<b>Power requirements</b>	
Operating voltage	12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V
Current consumption at 24 V DC	804mA
Current consumption at 48 V DC	75mA
Power output in Btu (IT) h	65.9
<b>Service</b>	
Diagnostics	LEDs (power, link status, data, error)
Redundancy functions	redundant 24 V power supply
<b>Ambient conditions</b>	
Operating temperature	0° to +60°C
Storage/transport temperature	-40° to +70°C
Relative humidity (non-condensing)	10% to 95%
MTBF	29.2 years (MIL-HDBK-217F)
<b>Mechanical construction</b>	
Dimensions (W x H x D)	110 x 131 x 111
Mounting	DIN Rail
Weight	680 g
Protection class	IP20
<b>Mechanical stability</b>	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min.; 0.7g, 13.2 Hz - 100 Hz, 90 min.; 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min.; 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
<b>EMC interference immunity</b>	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2kV (line/earth), 1kV (line/line), 1kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
<b>EMC emitted immunity</b>	
FCC CFR47 Part 15	FCC CFR47 Part 15
EN 55022	EN 55022 Class A
<b>Approvals</b>	

Safety of industrial control equipment	cUL 508
Hazardous locations	cUL 1604 Class1 Div 2
<b>Scope of delivery and accessories</b>	
Scope of delivery	Device, terminal block, operating manual
Accessories to order separately	Rail power supply RPS 30, RPS 80 EEC or RPS 120 EEC, 19" installation frame